

Tri-Max

New



Heavy duty stubble cultivator
3.00 - 4.10 m

Tri-Max is a new heavy duty stubble cultivator. **Tri-Max** consists of 3 rows of tines, angled levelling discs and a T-ring roller. A full cut is achieved when the implement is fitted with 300 mm wide winged shares. The specially designed share perfectly incorporates the stubble and plant residues. The 85 cm clearance height allows large volumes of trash to flow through the machine even at working depths of 25 cm. The angled discs mix the residue with soil and leave the surface level and smooth. The T-ring roller controls the depth and consolidates the ground.



Tri-Max NSH is mounted with the new developed 2-D tine, which turns 20 cm horizontal and 30 cm vertical. For working deeper, down to 30 cm, the implement can be fitted with the narrow points, 50x20 mm

600 mm T-ring roller: 50x50x6 mm T-steel
Tri-Max 410 and 580: 70x70x8 mm T-steel.

Optional: (3 m model)
400 mm flat steel crumbler
For mounting behind the
T-ring roller.



Tri-Max Classic with shear bolts:

Type	Working width	Nos of tines	Nos of discs	Weight	Hp required
300	3,00 m	11 pcs.	8 pcs.	1550 kg	125 hp
410-Hydr.	4,10 m	15 pcs.	11 pcs.	2460 kg	175 hp

Tri-Max Plus NSH 2-D stone security:

Type	Working width	Nos of tines	Nos of discs	Weight	Hp required
300	3,00 m	11 pcs.	8 pcs.	2050 kg	125 hp
410-Hydr.	4,10 m	15 pcs.	11 pcs..	3000 kg	175 hp